

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A system for dividing a single mass flow into two or more secondary flows of desired ratios, comprising:

A) an inlet adapted to receive the single mass flow, wherein the inlet is free of any flow meters for providing a measurement of flow through the inlet;

B) at least two secondary flow lines connected to the inlet, each flow line including,

a flow meter measuring flow through the flow line and providing a signal indicative of the measured flow, and

a valve controlling flow through the flow line based upon a signal indicative of desired flow rate;

C) a user interface adapted to receive at least one desired ratio of flow; and

D) a controller connected to the flow meters, the valves, and the user interface, and programmed to,

receive the desired ratio of flow through the user interface,

receive the signals indicative of measured flow from the flow meters,

calculate an actual ratio of flow through the flow lines based upon the

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

measured flow, wherein said calculation is made without reference to a measured flow through the inlet,

compare the actual ratio to the desired ratio,

calculate the desired flow through at least one of the flow lines if the actual ratio is unequal to the desired ratio, and

provide a signal indicative of the desired flow to at least one of the valves.

2. (Original) A system according to claim 1, wherein the flow meters are thermal-based.

3. (Original) A system according to claim 1, wherein:

the flow lines comprise first and second flow lines; and

the controller is programmed to,

provide a signal to the valve of the first flow line indicative of a first desired flow,

calculate a second desired flow if the actual ratio is unequal to the desired ratio, and

provide a signal to the valve of the second flow line indicative of the second desired flow.

4. (Original) A system according to claim 3, wherein the first desired flow causes the valve of the first line to fully open.

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

5. (Original) A system according to claim 3, wherein the ratio of flow is equal to the flow through the second flow line divided by the flow through the first flow line.

6. (Original) A system according to claim 5, wherein an allowable range for the desired ratio of flow is between about 1 and about 10.

7. (Original) A system according to claim 1, wherein:

the flow lines comprise first, second and third flow lines;

the user interface is adapted to receive a desired ratio of flow for the second and the first flow lines, and a desired ratio of flow for the third and the first flow lines; and

the controller is programmed to,

provide a signal to the first valve indicative of a first desired flow,

receive the desired ratios of flow through the user interface,

receive the signals indicative of measured flow from the flow meters,

calculate an actual ratio of flow for the second and the first flow lines based upon the measured flows through the second and the first flow lines,

calculate a second desired flow if the actual ratio for the second and the first flow lines is unequal to the desired ratio for the second and the first flow lines,

provide a signal to the valve of the second flow line indicative of the second desired flow,

calculate an actual ratio of flow for the third and the first flow lines based

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

upon the measured flows through the third and the first flow lines,

calculate a third desired flow if the actual ratio for the third and the first flow lines is unequal to the desired ratio for the third and the first flow lines, and

provide a signal to the valve of the third flow line indicative of the third desired flow.

8. (Original) A system according to claim 7, wherein the first desired flow causes the valve of the first line to fully open.

9. (Original) A system according to claim 7, wherein the first ratio of flow is equal to the flow through the second flow line divided by the flow through the first flow line, and the second ratio of flow is equal to the flow through the third flow line divided by the flow through the first flow line.

10. (Original) A system according to claim 9, wherein an allowable range for each desired ratio of flow is between about 1 and about 10.

11. (Canceled)

12. (Original) A system according to claim 1, further comprising a pressure sensor measuring pressure in one of the inlet and the secondary flow lines, and connected to the controller to provide the pressure measurement to the controller.

13. (Original) A system according to claim 12, wherein the pressure sensor measures pressure in the inlet.

14. (Previously canceled)

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

15. (Previously canceled)

16. (Currently amended) A method for dividing a single mass flow into two or more secondary mass flows of desired ratios, comprising:

A) receiving a single mass flow into an inlet and dividing the single mass flow into at least two flow lines connected to the inlet, wherein the inlet is free of any flow meters for providing a measurement of flow through the inlet;

B) measuring mass flow through each flow line;

C) receiving at least one desired ratio of mass flow;

D) calculating an actual ratio of mass flow through the flow lines based upon the measured flows, wherein said calculation is made without reference to a measured flow through the inlet;

E) calculating a desired flow through at least one of the flow lines if the actual ratio does not equal the desired ratio; and

F) regulating the flow line to the desired flow.

17. (Original) A method according to claim 16, wherein:

the single mass flow is divided into first and second flow lines;

the first flow line is regulated to a first desired flow;

a second desired flow is calculated using the desired ratio and the first desired flow if the actual ratio is unequal to the desired ratio; and

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

the second flow line is regulated to the second desired flow.

18. (Original) A method according to claim 17, wherein the first desired flow causes the first line to be fully open.

19. (Original) A method according to claim 17, wherein the ratio of flow is equal to the flow through the second flow line divided by the flow through the first flow line.

20. (Currently amended) A method according to claim ~~21~~ 16, wherein an allowable range for the desired ratio of flow is between about 1 and about 10.

21. (Original) A method according to claim 16, wherein:

the single mass flow is divided into first, second and third flow lines;

first and second desired ratios of mass flow are received;

the first flow line is regulated to a first desired flow;

a second desired flow is calculated using the first desired ratio and the first desired flow if the actual ratio of the first and the second flow lines is unequal to the desired first ratio;

the second flow line is regulated to the second desired flow;

a third desired flow is calculated using the second desired ratio and the first desired flow if the actual ratio of the first and the third flow lines is unequal to the desired second ratio; and

the third flow line is regulated to the third desired flow.

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

22. (Original) A method according to claim 21, wherein the first desired flow causes the first line to be fully open.

23. (Original) A method according to claim 21, wherein the ratios of flow of the first and the second flow lines are equal to the flow through the second flow line divided by the flow through the first flow line, and the ratios of flow of the first and the third flow lines are equal to the flow through the third flow line divided by the flow through the first flow line.

24. (Original) A method according to claim 23, wherein an allowable range for each of the desired ratios of flow is between about 1 and about 10.

25. (Original) A method according to claim 16, wherein mass flows are measured using thermally-based flow meters.

26. (Previously canceled)

27. (Original) A method according to claim 16, further comprising measuring pressure in one of the inlet and the secondary flow lines.

28. (Original) A method according to claim 27, wherein pressure in the inlet is measured.

29. (Previously canceled)

30. (Previously canceled)

31. (Previously added) A system according to claim 1, wherein the signal indicative of the desired flow to at least one of the valves comprises an orifice setting of the valve.

Appl. Serial No.: 10/816,084
Amendment dated December 28, 2004
Reply to Office action of September 28, 2004

32. (Previously added) A method according to claim 16, wherein a desired orifice setting for the flow line is calculated to produce the desired flow, and an orifice setting of the flow line is regulated to match the desired orifice setting.

33. (Previously added) A system according to claim 31, wherein the orifice setting of the valve is maintained by regulating either current or voltage through a solenoid.

34. (Previously added) A method according to claim 32, wherein an orifice setting of the flow line is regulated by regulating either current or voltage through a solenoid.